

Claims

1. A method for providing transitory audio information that is subject to interruption without appreciable loss of content, comprising the steps of:
 - receiving transitory audio information from an audio source;
 - 5 audibly providing the transitory audio information until an interrupt signal is received;
 - buffering the transitory audio information;
 - audibly providing a message that is associated with the interrupt signal; and
 - 10 audibly providing the buffered transitory audio information upon conclusion of the message.
2. The method of claim 1, wherein the buffered transitory audio information is provided at a faster rate than new transitory audio information is being received.
3. The method of claim 1, wherein the interrupt signal is initiated by the actuation of a repeat function and the message corresponds to a predetermined portion of the buffered transitory audio information.
4. The method of claim 1, wherein the message is a route instruction.
5. The method of claim 1, wherein the message is a collision warning.
6. The method of claim 1, wherein the buffered transitory audio information is stored in a compressed format.

FOIEB-01403460

7. The method of claim 1, further including the step of:
clearing the buffered transitory audio information when a
different audio source is selected.

8. The method of claim 1, wherein the transitory audio
information is provided in the form of a radio broadcast.

9. The method of claim 1, wherein the transitory audio
information is buffered in response to the interrupt signal.

~~10.~~ An automotive information system for providing
transitory audio information that is subject to interruption without appreciable
loss of content, comprising:

- 5 a receiver for receiving transitory audio information from an
audio source;
- a memory subsystem for storing data;
- an audio output device;
- a processor coupled to the receiver, the memory subsystem and
the audio output device; and
- 10 processor executable code stored within the memory subsystem
for causing the processor to perform the steps of:
 - providing the transitory audio information to the audio
output device until an interrupt signal is received;
 - buffering the transitory audio information within the
 - 15 memory subsystem;
 - providing a message that is associated with the interrupt
signal to the audio output device; and
 - providing the buffered transitory audio information to
the audio output device upon conclusion of the message.

11. The system of claim 10, wherein the buffered transitory audio information is provided at a faster rate than new transitory information is being received.

12. The system of claim 10, wherein the interrupt signal is initiated by the actuation of a repeat function and the message corresponds to a predetermined portion of the buffered transitory audio information.

13. The system of claim 10, wherein the message is a route instruction.

14. The system of claim 10, wherein the message is a collision warning.

15. The system of claim 10, wherein the buffered transitory audio information is stored in a compressed format.

16. The system of claim 10, wherein the processor executable code causes the processor to perform the additional step of:
clearing the buffered transitory audio information from the memory subsystem when a different audio source is selected.

17. The system of claim 10, wherein the audio source is a radio station and the transitory audio information is provided in the form of a radio broadcast.

18. The system of claim 10, wherein the transitory audio information is buffered in response to the interrupt signal.

09780710-021201

19. An audio information system for providing transitory audio information that is subject to interruption without appreciable loss of content, comprising:

- a radio receiver for receiving transitory audio information in the form of a radio broadcast from a radio station;
- a memory subsystem for storing data;
- an audio output device;
- a processor coupled to the receiver, the memory subsystem and the audio output device; and
- processor executable code stored within the memory subsystem for causing the processor to perform the steps of:
 - providing the transitory audio information to the audio output device until an interrupt signal is received;
 - buffering the transitory audio information within the memory subsystem;
 - providing a message that is associated with the interrupt signal to the audio output device; and
 - providing the buffered transitory audio information to the audio output device upon conclusion of the message.

20. The system of claim 19, wherein the buffered transitory audio information is provided at a faster rate than new transitory information is being received.

21. The system of claim 19, wherein the interrupt signal is initiated by the actuation of a repeat function and the message corresponds to a predetermined portion of the buffered transitory audio information.

22. The system of claim 19, wherein the message is a route instruction.

RECEIVED OCT 26 1980

23. The system of claim 19, wherein the message is a collision warning.

24. The system of claim 19, wherein the buffered transitory audio information is stored in a compressed format.

25. The system of claim 19, wherein the processor executable code causes the processor to perform the additional step of:

clearing the buffered transitory audio information from the memory subsystem when a different audio source is selected.

26. The system of claim 19, wherein the transitory audio information is buffered in response to the interrupt signal.

FILED OCT 20 2000